

GROUT PUMP



CSGP-2N/QR

Teesin Grout Pump are designed for most commercial available cementitious grouts. This manual type grout pump can be used in pumping cement grout to fill cracks and voids. With its size and weight advantage, it is easily portable and able to accomplish task where job is too small to justify sending out an engine-powered grouting rig, or the grout site that is hard to reach with full-size equipment.



CGP050Y



CSGP-1D



CSGP-20/QR



CSGP-2D

CSGP-2N/QR

Operating Weight: 23kg
Dimension (HxBxW):
1320mm x 970mm x 200mm
Output: 8L/min
Pressure: 8bar
Connection Hose Size:
in(inches)-1 out(inches)-1
Power Source: Manual

CSGP-20/QR

Operating Weight: 35kg
Dimension (HxBxW):
1500mm x 1150mm x 380mm
Output: 25L/min
Pressure: 10bar
Connection Hose Size:
in(inches)-1&1/2 out(inches)-1&1/4
Power Source: Manual

CSGP-20/WR

Operating Weight: 43kg
Dimension (HxBxW):
1500mm x 1430mm x 340mm
Output: 25L/min
Pressure: 10bar
Connection Hose Size:
in(inches)-1&1/2 out(inches)-1&1/4
Power Source: Manual

CSGP-1D

Operating Weight: 9kg
Dimension (HxBxW):
610mm x 560mm x 290mm
Output: 20L/min
Pressure: 1bar
Connection Hose Size:
in(inches)-1 out(inches)-1
Power Source: Manual

CSGP-2D

Operating Weight: 15kg
Dimension (HxBxW):
860mm x 600mm x 420mm
Output: 40L/min
Pressure: 1bar
Connection Hose Size:
in(inches)-1 out(inches)-1
Power Source: Manual

CGP050Y

Operating Weight: 24kg
Dimension (HxBxW):
788mm x 1118mm x 280mm
Output: 9L/min
Pressure: 14bar
Connection Hose Size:
in(inches)-2 out(inches)-2
Power Source: Manual